

ASIC/3 Features

- 32-bit ARM7 processor
- 100Mb Ethernet and optional wireless
- BACnet communication
- System Bus for ASI or BACnet MSTP communication
- Local Bus for ASI and/or Modbus Master RTU
- Compatible with Niagara, IntelliFront, and ASI WebLink
- USB Device Service Port
- Isolated switching power supply for AC or DC operation
- 10 Year hardware clock
- Two-part screw terminal input, output and power connections
- 8 Universal Inputs
- 8 Binary Relay Outputs
- 4 Analog Outputs
- NEMA-1 Industrial Control Panel
- Power Supply

ASI Controls ENC-9520 control panel is a complete package designed for energy management and control of mechanical systems. An ASIC/3-9520 configurable controller is mounted inside the panel.

The ASIC/3 Programmable System Controller represents a new generation of communicating distributed direct digital control for unitary equipment and building systems. The ASIC/3 controller is designed to be hardware compatible with the ASIC/2 Programmable controllers and offers expanded communication capability including USB, BACnet, Ethernet and Wireless.

The ASIC/3 provides energy management and control of a wide range of building systems including air handlers, chillers, cooling towers, boilers, pumps, lighting, etc. It has an isolated switching power supply for AC or DC operation and flash memory for program and data storage.

The controller is easily configured using ASI Visual Expert configuration software that links ready-made objects including scheduling, logic, PID control, alarming, optimum start, trending, run-time accumulation, and electrical demand management. The ASIC/3 has an on-board battery-backed calendar clock and allows special events, holidays, and schedules to be defined in advance. Configuration data is stored in non-volatile memory that is retained through power loss.

The ASIC/3 controller has two separate RS-485 system and local buses. The system bus is used to network multiple ASIC/3 and ASIC/2 controllers, or optionally the system bus can support BACnet MS/TP. The local bus can poll ASIC/1 terminal controllers and make control decisions based on the data received. No central system is needed to supervise the controller. Alternately the local bus can support Modbus Master RTU. Red and green LEDs indicate the controller's receive and transmit communications.

The ASIC/3 can operate as part of a larger communicating control network. The ASIC/3 offers Ethernet communication and alarm notification via wired 10/100 Mbps connection or optional WiFi module. The ASIC/3 also features a full-speed 12 Mbps USB Device connection for service in the field. The RS-485 connections support baud rates up to 57,600 bps, and standard BACnet MSTP baud rates up to 76,800 bps are also supported.

The eight 24 Vac relay outputs are ideal for driving contactors and starters. The four analog outputs are used for modulated actuators, electronic-pneumatic transducers, variable speed drives and other analog signal devices. The eight universal inputs may be used for counting pulses, for reading thermistors and contact closures directly, and for reading 4 to 20 mA, 0 to 10 Vdc or 1 to 5 Vdc input signals.



Features

Analog Inputs	Binary Inputs
Maintained Binary Outputs	Pulsed Outputs
Analog Outputs	
Scheduled Start/Stop	Afterhour Override
Calendar Events	Special Day Schedules
Multiple Control States	Multiple PID Loop
Counters and Timers	Optional Demand Limit
Conditional Logic	
Notify Alarm Configuration	Value Trending
Ethernet Communications	Optional Wireless
Remote Point Broadcast	Message Pass-thru
Local Bus Polling	Local Bus Broadcast
Hardware Clock	Brownout Protection
Optional Modbus Master RTU	
Optional BACnet MS/TP	

Specifications

Power Supply (Isolated)

Supply Voltage: 24 Vac +/- 15%, 50/60 Hz
or +/- 24 Vdc Power

Consumption: 27 VA (plus loads) Protection: PS8, Polyswitch, MOV

Connection: 2-part screw terminal

Indication: Red LED

Binary Outputs 8

Type: Form "A" Relay SPST N.O.
Dry Contacts

Voltage Rating: Class 2, 24 Vac or 24 Vdc

Current Rating: 1 A General Use

Connection: 2-part screw terminal

Indication: Red LED, Binary Outputs

Analog Outputs 4

Type: Analog 0-10Vdc

Resolution: 0.4% full scale

Current Rating: 20 mA

Protection: TVS, 10 V, 600W peak

Connection: 2-part screw terminal

Inputs 8

Type: Universal Analog/Binary

Range: 0 to 10 Vdc

Accuracy: 0.1% full scale

Connection: 2-part screw terminal

UL Listing

UL-916 Open Energy Management
Equipment File E123287 (PAXZ) Rated as a Class 2
Device Canada: C22.2 No. 205-M1983



CE

Meets CE requirements. EN 61326 Class A,
EN 61000-3-2 Class A and EN 61000-3-3
Complies with FCC Part 15 (CISPR 22) Class A

RS-485 Communications (2)

Format: RS-485 with optional 120 ohm Termination

Baud Rate: Up to 57,600 bps

Protection: 500 mW-s TVS with 100 mA Polyswitch

Maximum Length: 4000 ft (1.2 km) RS-485

Connection: 3 Position, screw terminals

Indication: Red LED Receive, Green LED Transmit

System Bus Communication

Address Range: 1 to 65535 except for group and global addresses

Maximum Size: Up to 64 devices with repeaters

Alternate Protocol: Modbus Master RTU

Local Bus Communication

ASI Address Range: 1 to 65535 except for group and global addresses

Maximum Size: Up to 64 devices with repeaters

Alternate Protocol: Modbus Master RTU

Ethernet Networking

Communication: UDP/IP or TCP/IP; auto-sense 10 Mbit/s or 100 Mbit/s
Note: Requires 100 MHz Ferrite Core on Ethernet cable.

Optional Wireless: IntelliFi wireless module or xBee wireless

Internal Power Supply

Supply Voltage: 120 Vac, 50/60 Hz

Panel

Panel: NEMA Type 1 Industrial Control Panel

Dimensions: 20" x 18" x 6"

Weight: approx. 22 lb (10 kg)

Panel UL Listed: E182943

Environmental

Operating: -20 to 45 °C (-4 to 113 °F)
10 to 95% RH non-condensing

Storage: -37 to 80 °C (-35 to +180 °F)
5 to 95% RH non-condensing

How to Order:	Order Number
Control Panel with Controller	ENC-9520

Accessories:	Order Number
Four Input Multiplex Kit	QUADMUX

Software & Documentation:	Order Number
ASI Expert Configuration Software	ASI Expert
ASIC/3 Object Definitions	ASIC3 OBJ DEF
ASIC/3 Installation Guide	ASIC3 Manual

